

ZONE WIRE CONNECTOR · P11V

Yellow winged wire nut

Type **Pressure-type wire connector** Color **Yellow** Wire range **18–10 AWG**

PACK LISTINGS

Pack size	Listing
500 pcs	UL 486C
1000 pcs	UL 486C · 600 V / 1000 V
100 pcs	UL 486C

PRINTED BOX-LABEL FACTS

Conductors	**Copper to copper**
Voltage	**600 V max building wiring; 1000 V max in fixtures and signs**
Install	**Pre-twisting unnecessary. Push wires in and screw on until two twists are visible in the wires.**
Temperature	**105°C (221°F) max**
Strip	**3/8 in (9.5 mm)**

PRODUCT FACTS

Flammability	**UL 94V-2**
Construction	**Winged housing with an internal square spring**
Material	**Polypropylene (PP)**

PRINTED WIRE COMBINATIONS · Solid and/or stranded

- 1 #10
- 1 to 3 #12
- 2 or 3 #14
- 2 to 4 #16
- 2 to 4 #18
- 1 #10 w/1 #12
- 1 #10 w/1 or 2 #14
- 1 #10 w/1 or 2 #16
- 1 #10 w/1 to 3 #18
- 1 #12 w/1 or 2 #14
- 1 #12 w/1 to 3 #16
- 1 #12 w/1 to 4 #18
- 1 #12 Sol w/5 #18 Sol
- 2 #12 w/1 or 2 #18
- 2 #12 w/1 #14
- 2 #12 w/1 #16
- 1 #14 w/1 to 4 #16
- 1 #14 w/1 to 5 #18
- 2 #14 w/1 to 3 #16
- 2 #14 w/1 to 3 #18
- 3 #14 w/1 #16
- 3 #14 w/1 or 2 #18
- 1 #16 w/1 to 5 #18
- 2 #16 w/1 to 4 #18
- 3 #16 w/1 to 3 #18
- 4 #16 w/1 or 2 #18