

ZONE WIRE CONNECTOR · P3

Orange wire nut

Type **Pressure-type wire connector** Color **Orange** Wire range **22–14 AWG**

PACK LISTINGS

Pack size	Listing
500 pcs	UL 486C

PRINTED BOX-LABEL FACTS

Conductors	**Copper to copper**
Voltage	**600 V max building wiring; 1000 V max in fixtures and signs (lower tier of combinations: 300 V max)**
Install	**Pre-twisting unnecessary. Push wires in and screw on until two twists are visible in the wires.**
Temperature	**105°C (221°F) max**
Strip	**5/16 in (7.9 mm); 3/8 in (9.5 mm) for #16 and smaller stranded wires**

PRODUCT FACTS

Flammability	**UL 94V-2**
Construction	**Insulated housing with an internal metal spring**

PRINTED WIRE COMBINATIONS · Solid and/or stranded

600 V max

- 1 or 2 #14
- 2 or 3 #16
- 2 to 4 #18
- 1 #14 w/1 #16
- 1 #14 w/1 #16 w/1 #18
- 1 #14 w/1 or 2 #18
- 1 #14 w/1 to 3 #20 or #22
- 1 #16 w/1 or 2 #18
- 1 #16 w/1 #18 w/1 #22
- 1 #16 w/1 to 3 #20 or #22
- 1 or 2 #16 w/1 #20 w/1 #22
- 2 #16 w/1 #18
- 2 #16 w/1 or 2 #20
- 2 #16 w/1 to 3 #22
- 1 #18 w/2 to 4 #20
- 1 #18 w/3 or 4 #22
- 1 or 2 #18 w/1 #20 w/1 #22
- 2 #18 w/1 or 2 #20 or #22
- 3 #18 w/1 #20 or #22

300 V max

- 4 #16
- 5 #18
- 3 to 5 #20
- 5 #22 Sol
- 5 #22 Str
- 3 #22 Sol w/2 #22 Str
- 1 #14 w/1 #16 w/1 #18
- 1 #14 w/2 #16
- 1 #14 w/3 #18
- 1 #14 w/4 #20
- 2 #14 w/1 #18
- 2 #14 w/1 to 3 #20 or #22
- 1 #16 w/4 #18
- 2 #16 w/2 or 3 #18
- 2 #16 w/3 #20
- 3 #16 w/1 #18
- 3 #16 w/1 or 2 #20 or #22
- 4 #16 w/1 #20 or #22
- 1 #18 w/1 #20
- 1 #18 w/5 #22
- 2 #18 w/3 #22
- 3 #18 w/2 #20 or #22
- 4 #18 w/1 #20 or #22
- 1 #20 w/4 #22
- 2 #20 w/2 or 3 #22
- 3 #20 w/1 or 2 #22
- 4 #20 w/1 #22